

MEETS AND EXCEEDS ALL NSF/ANSI STANDARDS 42 & 53

FOR THE REDUCTION OF SUBSTANCES LISTED BELOW:



Performance Data Sheet

Model: SC1500 FULL SPECTRUM CARTRIDGE

Filter tested to meet and exceed NSF/ANSI Standards 42 and 53 for the reduction of substances listed below.

Contaminant Reduction	Contaminant Challenge	Average Reduction	Capacity
Chlorine Taste and Odor	2.0 mg/L	99%	3300 gallons
Bacteria	E.Coli	99.999%	Life of Filter
Cysts	>50,000 cysts/L	ND 100% Removal	Life of Filter
Lead	150 ppb	95%	1500 gallons
Mercury	6 ppb	95%	1500 gallons
VOC's	300 ppb	95%	1500 gallons

Particulate Testing: Absolute Rated at 0.7 micron

Ceramic	Nominal Particle Size		
SC1500	0.3 to 0.5 micron	0.5 to 0.6 micron	0.6 to 0.8 micron
Efficiency	99.3% Removal	99.8% Removal	99.9% Removal

Service Flow	0.5 gpm
Water Supply	Potable
Water Pressure	60 psi
Water Temperature	40°F—100°F(4.4° C—37.8° C)

Performance Data testing performed by 3rd party for validation of specific performance claims.

IBR Chelsea, Michigan
Pace Analytical Minnesota

It is imperative that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See installation manual for warranty information.

NOTE: While the testing was performed under strict standard lab conditions, actual performance may vary.

Certified Products, backed by third party testing, manufactured to ISO9000 standards for quality and performance.



MADE IN USA